TECHNICAL DATA SHEET

RUBBER FLOORING FOR HORSE STABLES





TECHNICAL SPECIFICATION

Product	Resilient rubber flooring with a flat surface and liquid drainage pads underneath: 5 mm pads on 30 mm tiles, 15 mm pads on 40 mm tiles
Application	Horse stable boxes, stalls, walkways, wash and grooming areas, equine facilities
Material	SBR granulate in 5 colours (red, grey, green, blue, black), or SBR base with an EPDM top layer in 24 colours
Dimensions	500 × 500 mm, 500 × 1000 mm, 1000 × 1000 mm (tolerance ±2 mm)
Thickness	30 mm and 40 mm (tolerance ±2 mm)
Weight	30 mm: approx. 25.4 kg/m² · 40 mm: approx. 34.4 kg/m²
Density	900 kg/m³
Reaction to fire	EN 13501-1: SBR tile E_{fl}, EPDM tile D_{fl}
Slip resistance	DIN 51097, 24°: high slip resistance under wet conditions
VOC emissions	AgBB: pass

CE Marking according to EN 14041:2005.

BulletTrap Baltic · MB Murakana
Sudervės g. 12-3, Avižienių k., LT-14192 Vilniaus r., Lithuania
info@bullettrapbaltic.com · +370 682 38746 · EU-manufactured (Latvia), delivered across the EU

TECHNICAL DATA SHEET

RUBBER FLOORING FOR HORSE STABLES

Durable, safe and hygienic flooring for horse stables, stalls and equine facilities. It combines shock absorption, drainage and durability for a healthier and safer environment for horses and handlers. The tiles provide thermal and sound insulation and resist urine and horseshoes, so they last in demanding stable conditions.



APPLICATIONS

- Horse stable boxes
- Walkways and corridors
- Washing and shower areas
- Grooming areas
- Horse transport areas
- Equine training facilities

HORSE COMFORT AND SAFETY

- Shock-absorbing surface reduces stress on joints and hooves
- Slip-resistant texture for horses and staff
- Comfortable resting surface

HYGIENE

- Liquid-permeable design supports drainage
- Resistant to urine and moisture
- Reduces bedding consumption by up to 70 %

DURABILITY

- Heavy-duty rubber resistant to horseshoes and wear
- Long service life under intensive use
- Easy to clean and maintain

INSTALLATION

- Modular tiles for quick installation
- For concrete and other solid stable floors
- Single tiles can be replaced if needed

PRODUCT RANGE

PRODUCT	THICKNESS	DRAINAGE PADS	FORMAT	STANDARD COLOURS
Flat tile, 900 kg/m³	30 / 40 / 45 mm	5 / 15 / 15 mm	500 × 500, 500 × 1000, 1000 × 1000 mm	black, red
Puzzle tile, 900 kg/m³	22 / 25 / 30 mm	none / 5 mm / 5 mm	interlocking, covers 1.05 m² per tile	black, red
Wall protection panel, 930 kg/m³	8 / 10 mm	—	1020 × 1020 mm	black

Prices on request. Minimum order one pallet. Colour variations, fading and some black granules on the surface are possible. Request a quote: info@bullettrapbaltic.com

BulletTrap Baltic · MB Murakana
Sudervės g. 12-3, Avižienių k., LT-14192 Vilniaus r., Lithuania
info@bullettrapbaltic.com · +370 682 38746 · EU-manufactured (Latvia), delivered across the EU